

Ergonomic design meets style and convenience. The K-Series® for Ceros® safety helmets include Click-and-Go® magnetic, mechanical, and slot-adapted earmuff options for a simple, convenient accessory attachment option.



- 1 Slot adapted earmuffs
- 2 Click-and-Go® magnetic earmuffs
- 3 Earmuffs designed to work seamlessly with face shield
- 4 Lightweight with length adjustment options for various head shapes
- 5 Snug-fitting, soft foam ear cushions adapt to the surface and head shape of the wearer
- 6 360-degree rotation to nest tightly against Ceros® safety helmets

## Accessory compatibility

### Helmet accessories

Product Name	Part #	XP200	XP250	XP200E	XP250E	XP450A	XP450AE
K1C earmuffs	17-15001	◊	◊	◊ <sup>□</sup>	◊ <sup>□</sup>	◊	◊ <sup>□</sup>
K2C earmuffs	17-16001	◊	◊	◊ <sup>□</sup>	◊ <sup>□</sup>	◊	◊ <sup>□</sup>

### Face shield accessories

Product name	Part #	XP Mechanical	XP Magnetic	XA Magnetic	Ultrex®1
K1M earmuffs <sup>+</sup>	17-17001	◊ <sup>□</sup>	◊	◊	◊
K2M earmuffs <sup>+</sup>	17-17002	◊			◊
K2M magnet earmuffs <sup>+</sup>	17-18002		◊	◊	

<sup>+</sup>Requires a face shield or adapter purchase

<sup>□</sup>Warning: earmuffs are not dielectric

◊ = Compatible

### Earmuff accessories

Product name	Part #	K1C	K2C	K1M	K2M	K2M Magnetic	K1	K2	K3
Earmuff hygiene kit type 1	17-28001	◊					◊		
Earmuff hygiene kit type 2	17-29001		◊	◊	◊	◊		◊	◊

# K-Series®

## Ceros® safety helmet earmuffs

# HexArmor®

### Use with face shield

#### K1M earmuffs

17-17001

ANSI S3.19-1974 NRR 22 dB	Z94.2-2014 CSA Class A	EN 352-1 SNR: 29 dB, H: 33 dB, M: 26 dB, L: 19 dB
------------------------------	---------------------------	--

- Compatible with mechanical face shield



22  
dB

limited quantities available

#### K2M earmuffs

17-17002

ANSI S3.19-1974 NRR 25 dB	Z94.2-2014 CSA Class A	EN 352-1 SNR: 30 dB, H: 35 dB, M: 27 dB, L: 20 dB
------------------------------	---------------------------	--

- Compatible with mechanical face shield



25  
dB

#### K2M magnet earmuffs

17-18002

ANSI S3.19-1974 NRR 24 dB	Z94.2-2014 CSA Class A	EN 352-1 SNR: 30 dB, H: 35 dB, M: 27 dB, L: 20 dB
------------------------------	---------------------------	--

- Compatible with magnetic face shield



24  
dB

### Use without face shield – slot adapted

#### K1C earmuffs

17-15001

ANSI S3.19-1974 NRR 22 dB	Z94.2-2014 CSA Class B	EN 352-1 SNR: 27 dB, H: 32 dB, M: 24 dB, L: 17 dB
------------------------------	---------------------------	--



22  
dB

#### K2C earmuffs

17-16001

ANSI S3.19-1974 NRR 25 dB	Z94.2-2014 CSA Class A	EN 352-1 SNR: 30 dB, H: 35 dB, M: 27 dB, L: 20 dB
------------------------------	---------------------------	--



25  
dB

Call 1-877-MY ARMOR or visit [hexarmor.com](http://hexarmor.com)

Protective devices do not provide unlimited protection. Some operations may require machine guards, face shields, special filter lenses, or other safety equipment. Safety helmets do not provide complete protection against hazards, and should only be used in conjunction with the prescribed safety equipment for the application as well as defined safety practices.