

ZTEK®

Lightweight Polycarbonate One Piece Spectacle



Black Temples

Part	Lens
S2510S•••	Clear
S2510ST••••	Clear H2X Anti-Fog
S2514S•••	1.5 IR Filter
S2515S•••	Coffee
S2520S•••	Gray
S2520ST••••	Gray H2X Anti-Fog
S2530S•••	Amber
S2540S•••	Orange
S2550SF••	5.0 IR Filter

Black Temples

Part	Lens
S2560S•••	Infinity Blue
S2560SF••	3.0 IR Filter
S2560ST••••	Infinity Blue H2X Anti-Fog
S2565S••	Purple Haze
S2570S••	Silver Mirror
S2575S•••	Blue Mirror
S2580S•••	Indoor/Outdoor Mirror
S2590S••	Gold Mirror
S25ARCS••	Lens Coating blocks 75% of IR Radiation



















- Integrated nose piece.
- Soft, non-slip rubber temple tips provide non-binding fit.
- Economical wrap-around single lens provides full panoramic view.
- Lenses are coated for superior scratch resistance, provides 99.9% protection from harmful UV rays.

GENERAL SPECIFICATION

Bridge: 13mm
Lens Base: 10 Curve
Lens Size Diagonal: 64mm
Lens Size Vertical: 44mm
Lens Thickness: 2.5mm
Overall Length (Lens-Tip): 154mm
Overall Width (Hinge-Hinge): 137.5mm
PD: 68mm
Weight: 21gm

PACKAGING
Polybag: 1pc
Inner Box: 12 pcs
Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	Attractive & stylish unitary lens
Frame	Polycarbonate	Matted finish integral to lens
Side Shield	Polycarbonate	Integral to lens
Nose Piece	Polycarbonate	V bridge - integral to lens
Temple	Polycarbonate	Matte finish - straight back design
Temple Tips	PVC	Soft to prevent slippage
Hinge	Polycarbonate	3 barrel type, integral to frame
Screw	Stainless Steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
S2510S	 Clear	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2510ST	 Clear H2X Anti-Fog	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2514S	 1.5 IR Filter	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2515S	 Coffee	P Z87 + U6 L3	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2520S	 Gray	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2520ST	 Gray H2X Anti-Fog	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2530S	 Amber	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2540S	 Orange	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2550SF	 5.0 IR Filter	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2560S	 Infinity Blue	P Z87 + U6 L1.3	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2560SF	 3.0 IR Filter	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2560ST	 Infinity Blue H2X Anti-Fog	P Z87 + U6 L1.3	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2565S	 Purple Haze	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2570S	 Silver Mirror	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2575S	 Blue Mirror	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2580S	 Indoor/Outdoor Mirror	P Z87 + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-07
S2590S	 Gold Mirror	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-07
S25ARCS	 IR Filter	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3-07

LENS MARKING

Symbols:

P: Manufacturer's mark
 Z87: ANSI standard for Eye and Face protection devices
 +: High Impact
 H: Small Head Size
 S: Special Purpose
 W: Welding Filter

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%
 U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%
 U3: Max Effective Far UV= .07% / Max Near UV= 1.4%
 U4: Max Effective Far UV= .04% / Max Near UV= .5%
 U5: Max Effective Far UV= .02% / Max Near UV= .2%
 U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light
 L1.7: 55% Max. Visible Light
 L2.5: 29% Max. Visible Light
 L3: 18% Max. Visible Light

FRAME MARKING

Symbols:

P: Manufacturer's mark
 Z87: ANSI standard for Eye and Face protection devices
 +: High Impact
 P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices