

- SAFE
- RELIABLE
- ADAPTABLE

SUB-COMPACT SRL

USE IN PLACE OF YOUR LANYARD
TO REDUCE FALL DISTANCES

**SINGLE-LEG & DUAL-LEG
UNITS AVAILABLE**

ROGUE

sub-compact srl

ROGUE

a complete line of sub-compact self-retracting lifelines available in single and double unit models - 8' length



model MRG1-0Z
(actual size)



FCP
FrenchCreek
Production
Made in the U.S.A.

ROGUE FEATURES

Designed to be used as a connecting device in a personal fall arrest system, the sub-compact Rogue SRL connects the user's harness to the anchorage point. Each ROGUE unit is 8' in overall length.

The self-retracting lifeline provides freedom of movement to workers performing their job at various heights. As the worker moves toward or away from the device, the spring tensioned webbing will retract back into the unit or will draw out of it. The device automatically takes up the slack in the webbing keeping it out of the way while minimizing free fall distance should a fall occur. A centrifugal breaking mechanism minimizes free fall distance. A visual load indicator warns the user that the unit has been involved in a fall.

EASE OF ATTACHMENT

Attaches directly to the back of the harness. The single-leg unit attaches to the back D-ring, while the dual-leg unit attaches through the webbing loop below the back D-ring, keeping the back D-ring free for other possible connections.

Single-Leg Connection



Dual-Leg Connection



SWIVEL ANCHOR LOOP

Swivels 360° to help limit line twisting for smooth operation.

LIGHT DURABLE SUB-COMPACT HOUSING

High-strength, light weight, sub-compact housing provides excellent durability. Starting at 1.9 lbs, these units are light enough to replace your lanyard to improve safety performances.

IMPACT INDICATOR

Featuring an inline tear away impact indicator, that allows for visible inspection of the slightest falls into the unit. The indicator will show wear prior to the shock absorber being engaged!

SHORT FALL ARREST ACTIVATION

Unit will stop a fall within inches, reducing fall distances and reducing fall arrest forces to 900 lbs or less.

EXTREMELY VERSATILE

The full line of ROGUE SRL's offers a variety of options, providing a unit for every jobsite.

WEBBING SHOCK PACK

The shock pack is designed to tear-away if the unit is fallen into, helping to reduce fall-arrest forces.

400 LB. WEIGHT CAPACITY

ROGUE SRL units offer a 400 lb total weight capacity for worker and tools.

TRACKER CAPABLE

FCP's RFID tracking system is available on the ROGUE. Simply add "ID" to the part number.

NUMEROUS SNAPHOOK OPTIONS

There are many options for snap hooks available for both the housing/swivel connection (at top of unit) and the lifeline connection (at the bottom of the unit).

MEETS OR EXCEEDS INDUSTRY STANDARDS

- ◆ OSHA Subpart M 1926.502, 1940.66
- ◆ ANSI A10.32-2012, Z359.14-2012
- ◆ "Class A" SRL



ROGUE PART NUMBERS & ORDERING OPTIONS

ROGUE SRL Single-Leg Model Selections

Single-Leg Model #	Housing/Swivel Connector	Lifeline Connector	Weight (lbs)
MRG3-0Z	#354-4 1" opening, steel carabiner	#Z74 3/4" steel locking snap	3.1
MRG3-0SZ	#354-4 1" opening, steel carabiner	#RL-28 3/4" steel swivel locking snap	3.3
MRG3-4Z	#354-4 1" opening, steel carabiner	#Z136 2 1/4" steel locking rebar snap	3.9
MRG0Z-0Z	#Z74 3/4" steel locking snap	#Z74 3/4" steel locking snap	3.3
MRG0Z-4Z	#Z74 3/4" steel locking snap	#Z136 2 1/4" steel locking rebar snap	4.1
MRG3A-6A	#354-2A 7/8" aluminum carabiner	#63A 3/4" aluminum captive-eye carabiner	2.2
MRG3A-8A	#354-2A 7/8" aluminum carabiner	#62A 2" aluminum locking carabiner	2.9
MRG4Z-0SZ	#Z136 2 1/4" steel locking rebar snap	#RL-28 3/4" steel swivel locking snap	4.3
MRG1-0Z	Swivel Anchor Loop Only	#Z74 3/4" steel locking snap	2.4
MRG1-0SZ	Swivel Anchor Loop Only	#RL-28 3/4" steel swivel locking snap	2.6
MRG1-4Z	Swivel Anchor Loop Only	#Z136 2 1/4" steel locking rebar snap	3.2
MRGCM-0Z	Cab Mount	#Z74 3/4" steel locking snap	3.2
MRGCM-0SZ	Cab Mount	#RL-28 3/4" steel swivel locking snap	3.4

* If you are interested in a snap hook combination not listed, please inquire.

ROGUE SRL Dual-Leg Model Selections

Dual-Leg Model #	Housing/Swivel Connector	Lifeline Connector	Weight (lbs)
M2RG-0Z	#354-6TL 1/2" steel triple-lock carabiner	#Z74 3/4" steel locking snap	3.7
M2RG-0SZ	#354-6TL 1/2" steel triple-lock carabiner	#RL-28 3/4" steel swivel locking snap	4.2
M2RG-4Z	#354-6TL 1/2" steel triple-lock carabiner	#Z136 2 1/4" steel locking rebar snap	5.3
M2RG-6A	#354-6TL 1/2" steel triple-lock carabiner	#63A 3/4" aluminum captive-eye carabiner	2.7
M2RG-8A	#354-6TL 1/2" steel triple-lock carabiner	#62A 2" aluminum locking carabiner	4.0

* To order RFID TRACKER capable units, simply add "ID" to the part number.

ROGUE LIFELINE / ANCHOR HOOK OPTIONS

 <p>Z74</p> <p>Locking snap: Steel, 3.6K, 3/4" gate, meets ANSI Z359.1-2007</p>	 <p>RL-28</p> <p>Locking snap w/ impact indicator: Steel, swivel, 3/4" gate, meets ANSI Z359.1-2007</p>	 <p>Z136</p> <p>Locking rebar snap: Steel, 3.6K, 2 1/4" gate, meets ANSI Z359.1-2007</p>	 <p>354-4</p> <p>Twist lock carabiner: Steel, 1" gate, meets ANSI Z359.1-2007</p>	 <p>354-6TL</p> <p>Twist lock carabiner: Steel, 3/4" gate, meets ANSI Z359.1-2007</p>
 <p>74AZ</p> <p>Locking snap: Aluminum, 3.6K 3/4" gate, meets ANSI Z359.1-2007</p>	 <p>63A</p> <p>Twist lock captive eye carabiner: Aluminum, 3.6K, 3/4" gate, meets ANSI Z359.1-2007</p>	 <p>62A</p> <p>Twist lock scaffold hook: Aluminum, 2" gate</p>	 <p>354-2A</p> <p>Twist lock carabiner: Aluminum, 7/8" gate</p>	 <p>Cab Mount</p> <p>Cab mount bracket attaches SRL to cab, offering a convenient anchor point.</p>

FrenchCreek

FALL SAFETY EQUIPMENT

AMERICAN MADE. AMERICAN OWNED.

100 North Thirteenth Street • Franklin, PA 16323 • Toll Free: 877.228.9327 • 814.437.1808

fax: 814.437.2544 • fcp@velocity.net • www.frenchcreekproduction.com



Dual-leg
ROGUE SRL
shown on
STRATOS Harness
#22870

Distributed by:

www.frenchcreekproduction.com