



Husky Bladder Tanks

Bladder Specifications

- Sizes 25 Gal. Up To 50,000 Gal.
- Manufactured To Meet Military Or Commercial Specifications
- Materials: XR's, PVC's, Urethanes (MIL Spec)
- Fittings: PVC (NSF 61), Aluminum, Stainless Steel, Brass
- Fitting Sizes From .75" - 6"
- All Stainless Steel Hardware On All Husky Bladders
- Access Panels
- Maneuvering Straps Near The Corners And Every 5' Down The Sides
- Flame Arrestors
- Double "T" Style Vents And Mushroom Vents
- Stringent Quality Control Department. All Husky Bladders Are Tagged, Signed And Dated With Inspection Labels
- Storage Bags Included
- Optional Ground Covers And Sunscreens In Various Weights
- Field Repair Kits
- In House Repairs
- Auto Cad Design
- 10 Year Manufacturer's Warranty
- CALL FOR BLADDER BERM PRICING!



5,000 and 10,000 gal. Bladders Being Tested Before Shipping



20,000 Gal. Diesel Fuel Bladder Tank Farm In Alaska

10,000 Gal. Fuel Bladder Inside A Husky Bladder Berm



50,000 Gal. Pillow Tank



Husky Specializes In Truck Bladder Tanks

Husky Portable Containment will manufacture custom bladder or pillow tanks to meet your requirements and specifications. We can build them taller, shorter, wider or longer with virtually any fitting and valve configuration you can come up with. You tell us what you need and our design team will create your custom bladder tank in Auto Cad.

Husky Bladder Tank Sizes and Weights

Husky uses PVC—22 oz., and 30 oz. / Urethanes—28 oz. up to 50 oz. / All XR-5 products and XR-3PW (potable).
 All Bladder Tank Part Numbers begin with, BT-, and are determined by size, material type and ounces per sq. yd.
 Material symbols; PVC = V, XR-5 8130 = XR30, XR-3PW 8130 (potable) = PW30, Urethane = U, Urethane potable = UPW
 Part No. Examples;

BT-25V22 (25 gal. 22 oz. pvc), BT-25XR30 (25 gal. XR-5 8130), BT-25U40 (25 gal. 40 oz. Urethane), BT-25UPW40 (Potable 40 oz. Urethane)
 These weights below are determined using 30 per sq. yd. material, 20,000 gal. and over using 40 oz. Filled sizes can be altered in LWH

Part No.	Capacity US Gal./ Imp Gal./ Liters	Approx. Filled Size STD / Metric	Approx. Folded Size STD / Metric	Empty Weight lbs. / kg.	Shipping Weight lbs. / kg.
BT-25V30	25 / 21 / 95	24" x 36" x 8" / .6m x .9m x .2m	14" x 18" x 6" / .4m x .5m x .15m	10 lbs. / 4.5 kg	14 lbs. / 6.4 kg *
BT-50V30	50 / 42 / 189	36" x 52" x 9" / .9m x 1.3m x .2m	15" x 21" x 7" / .4m x .5m x .15m	14 lbs. / 6.4 kg	18 lbs. / 8.2 kg *
BT-75V30	75 / 63 / 284	42" x 54" x 9" / 1m x 1.4m x .2m	20" x 22" x 7" / .5m x .6m x 1.5m	16 lbs. / 7.3 kg	20 lbs. / 9 kg *
BT-100V30	100 / 83 / 376	48" x 66" x 9" / 1.2m x 1.7m x .2m	22" x 25" x 7" / .6m x .6m x 1.5m	19 lbs. / 8.6 kg	23 lbs. / 10.4 kg *
BT-150V30	150 / 125 / 568	60" x 60" x 12" / 1.5m x 1.5m x .3m	22" x 26" x 8" / .6m x .7m x .2m	22 lbs. / 10 kg	26 lbs. / 11.8 kg *
BT-250V30	250 / 208 / 946	60" x 84" x 14" / 1.5m x 2.1m x .4m	22" x 32" x 8" / .6m x .8m x .2m	27 lbs. / 12.3 kg	31 lbs. / 14 kg *
BT-500V30	500 / 416 / 1892	84" x 108" x 16" / 2.1m x 2.7m x .4m	25" x 32" x 9" / .6m x .8m x .2m	33 lbs. / 15 kg	37 lbs. / 16.8 kg *
BT-750V30	750 / 625 / 2839	99" x 114" x 16" / 2.5m x 2.9m x .4m	25" x 35" x 9" / .6m x .9m x .2m	49 lbs. / 22.2 kg	53 lbs. / 24 kg *
BT-1000V30	1000 / 833 / 3785	9' x 11' x 16" / 2.7m x 3.4m x .4m	40" x 48" x 14" / 1m x 1.2m x .4m	60 lbs. / 27.2 kg	95 lbs. / 43 kg
BT-1250V30	1250 / 1041 / 4731	9'6" x 12'4" x 18" / 2.9m x 3.8m x .5m	40" x 48" x 14" / 1m x 1.2m x .4m	68 lbs. / 30.9 kg	103 lbs. / 46.7 kg
BT-1500V30	1500 / 1249 / 5678	10' x 14' x 18" / 3m x 4.3m x .5m	40" x 48" x 15" / 1m x 1.2m x .4m	78 lbs. / 35.4 kg	113 lbs. / 51.3 kg
BT-2000V30	2000 / 1666 / 7570	10'6" x 14'6" x 22" / 3.2m x 4.4m x .6m	40" x 48" x 18" / 1m x 1.2m x .5m	82 lbs. / 37.2 kg	117 lbs. / 53 kg
BT-2500V30	2500 / 2082 / 9463	12' x 14'6" x 24" / 3.7m x 4.4m x .6m	40" x 48" x 18" / 1m x 1.2m x .5m	91 lbs. / 41.3 kg	126 lbs. / 57.2 kg
BT-3000V30	3000 / 2498 / 11355	13'6" x 15' x 24" / 4.1m x 4.6m x .6m	40" x 48" x 22" / 1m x 1.2m x .6m	105 lbs. / 47.6 kg	140 lbs. / 63.5 kg
BT-4000V30	4000 / 3330 / 15140	14' x 18' x 27" / 4.3m x 5.5m x .7m	40" x 48" x 24" / 1m x 1.2m x .6m	128 lbs. / 58.1 kg	162 lbs. / 73.5 kg
BT-5000V30	5000 / 4164 / 18925	15'6" x 19'6" x 27" / 4.7m x 5.9m x .7m	40" x 48" x 26" / 1m x 1.2m x .7m	159 lbs. / 72.1 kg	194 lbs. / 88 kg
BT-6000XR30	6000 / 4996 / 22710	16'6" x 20' x 30" / 5m x 6m x .8m	40" x 48" x 28" / 1m x 1.2m x .7m	197 lbs. / 89.4 kg	232 lbs. / 105.2 kg
BT-10000XR30	10000 / 8327 / 37850	20' x 24' x 36" / 6m x 7.3m x .9m	40" x 48" x 30" / 1m x 1.2m x .8m	284 lbs. / 128.8 kg	324 lbs. / 147 kg
BT-20000U40	20000 / 16654 / 75700	22' x 31' x 48" / 6.7m x 9.5m x 1.2m	42" x 48" x 48" / 1.1m x 1.2m x 1.2m	551 lbs. / 250 kg	626 lbs. / 284 kg
BT50000U40	50000 / 41635 / 189250	30' x 46' x 60" / 9.1m x 14m x 1.5m	48" x 72" x 56" / 1.2m x 1.8m x 1.4m	1017 lbs. / 461 kg	1092 lbs. / 495 kg

* = will ship UPS

Husky Bladder Tanks



Bladder tanks have many have many practical uses:

- Drinking water storage for disaster area victims (NFS 61 Approved)
- Waste water storage (Gray Water)
- Rainwater collection tanks for irrigation systems
- Nurseries
- Agricultural. Livestock watering or insecticide application
- Fire Fighting
- Gray water storage for pressure washing and recovery systems
- Black water storage (Sewage)
- Recreational vehicle tanks. Drinking water and black water storage
- Pickup truck tanks
- Flat bed truck tanks for transportation of drinking water, waste water
- Railcar tanks
- Fuel storage tanks. Diesel, Jet A, etc.
- Food grade products such as, molasses, wine, olive oil, vegetable oil, etc.

Husky offers many types of fittings that can be installed on our bladder tanks. If we don't manufacture it we can get it. The majority of our flanges, swivel couplings, access plates and fittings are manufactured by us to ensure our commitment to quality control.

Fittings & Valves—

- Sizes .75" - 6", Male or Female rigid threads
- Fire Hose Threads (Female swivels w/NH threads available)
- Ball Valves—PVC, Brass, Stainless Steel
- Camlock Fittings—PVC, Aluminum, Brass, Stainless Steel
- Flanges—PVC, Aluminum, Stainless Steel. Female or Male Threads
- Storz Fittings 2" to 6"
- Flame Arrestors
- Vents—Aluminum Double "T" Style, PVC with Screen
- Access Panels
- Manway Covers
- Pressure Relief
- All Types of Hoses Available—PVC, NSF 61, Fuel Grade
- All Sizes and Types of Pumps Available—Water Transfer, Fuel Transfer



Husky Bladder Tanks are built with quality and precision in mind. We use only top quality first grade materials for all our bladder tanks. Every Husky Bladder Tank is tested and approved by one of our quality control team. All bladders when leaving our facility will be tagged with an inspection ticket showing the date of the test, part no. and the inspectors initials. Husky has an unprecedented 10 year manufacturer's warranty on all welded seams.

Put A Husky Bladder Tank On Your Team Today!