

Making Locating Easier Since 1953 100% EMPLOYEE-OWNED COMPANY



# **Multi-Frequency** Pipe & Cable Locator

- **Ultralight Design**
- **Compact & Portable**
- **Pinpoint Accuracy**







**3 FREQUENCIES • 1 LOCATOR • ALL UTILITIES** 
















## **Receiver** + **X**mitter











Slim, Sleek & Powerful Transmitter: 3.5 lbs and 1.75" thick

#### **Receiver** Specifications

Operating Frequency: Active: 512 Hz, 33 kHz and 82 kHz

Passive: 50 or 60 Hz Sonde: 512 Hz

Battery: One 9V Alkaline Battery

Battery Life: 12 Hours (intermittent use)

Weight (incl. battery): 2.8 lbs (1.25 kg)

Operating Temperature: -4°F to 140°F (-20°C to 70°C)

Water and Dust Resistance: Rated IP54

Overall Dimensions: Closed: 17.5 in (~44 cm)

Extended: 27.7 in (~70 cm)

Max. Depth Capability: Approximately 19' (5.8 m)

Sonde mode - approximately 5' - 15'

(1.5 m to 4.2 m)

#### **Transmitter** Specifications

Operating Frequency: 512 Hz, 33 kHz and 82 kHz

Operating Modes: Conductive, Inductive, and Inductive Clamp

 Max. Output Power:
 512 Hz - 1/2, 1, 2 or 5 W

 (Conductive mode
 33 kHz - 1/2, 1, 2 or 5 W

 @ 1000 Ω load)
 82 kHz - 1/2 or 1

Battery Type: Rechargeable NiMH pack (12V)

**Battery Life:** 8 Hours (intermittent usage @ 70° F)

**Charging:** Internal Smart Charger powered by

AC/DC power adapter

**Dimensions:** 10"W x 10.25"D x 1.75" H

(25.4 cm x 26 cm x 4.5 cm)

**Weight:** 3.5 lbs (1.6 kg)

Operating Temp.: -4°F to 140°F (-20°C to 70°C)

**Backlighting:** White LED array **Water and Dust Resistance:** Rated IP54



### How does Rex stack up to the competition?

A new slim and ultralight transmitter is combined with a retractable receiver to make Rex the most user-friendly and affordable multi-frequency locator on the market. See how Rex stacks up in **low** price and **high** performance here: schonstedt.com/rex (or just scan the QR code)



Contact Us: 800-999-8280 info@schonstedt.com

Find Your Local Dealer: **schonstedt.com** 







