

HEXARMOR® VS300

Tri-component design paired with innovative features

Triple-injection molded hard and soft components

Flexible side arms with 7 inclination levels

Brow guard provides protection from flying particles, dirt or dust

Metal-free

Soft ear pieces guarantee a stable and low pressure fit

LTX® Lens Technology for premium optical clarity

Soft flex nose loops ensure even weight distribution on nose bridge

Attachable foam guard available

100% UV protection



Made in Germany

PART NUMBERS:

Lens	Coating	Part Number
Clear	TruShield®	11-19001-02
Clear	TruShield®2F	11-19002-03
Anti-Reflective	Anti-Reflective	11-19003-07
Variomatic	TruShield®	11-19004-08
Clear Add+1.0	TruShield®	11-19005-09
Amber	TruShield®	11-19006-02
Grey 23%	TruShield®	11-19007-02
Silver Mirror 12%	Anti-fog inside	11-19008-06
Clear Add+2.0	TruShield®	11-19009-10
Variomatic Dark	TruShield®	11-19010-08
Attachable Foam Guard		14-10019

COATING DESCRIPTIONS:

Coating	Interior	Exterior	Use
TruShield®	Permanent anti-fog	Scratch resistant hard coat	Multipurpose
TruShield®2F	Permanent anti-fog and scratch resistance	Permanent anti-fog and scratch resistance	Hot to cold, cold to hot transition for moderately dirty environments
TruShield® Variomatic	Permanent anti-fog	Scratch resistant hard coat	Self-tinting (dark within 10 seconds, lighter within 30 seconds)
Anti-Reflective	Scratch resistant	Scratch resistant	Optimum anti-reflective protection with high degree of light transmission

Standards

ANSI Z87.1-2015
High Impact Rated Z87+
CE EN166
CSA Z94.3*
*With exception of Add+1.0

Case Quantities

12 pair per case
192 per carton
*Clear Add+ 1.0 has 10 pair per case and 160 per carton

Call 1-877-MY ARMOR or visit hexarmor.com

HexArmor
EYEWEAR

Protective devices do not provide unlimited protection. Some operations may require machine guards, face shields, special filter lenses, or other safety equipment. Safety eyewear does not provide complete protection against hazards, and should only be used in conjunction with the prescribed safety equipment for the application as well as defined safety practices.