Proper fit & care for your Ceros[®] safety helm<u>et</u>

Hex/Armor

How should your safety helmet fit?

Use these tips to ensure your HexArmor® Ceros® safety helmet fits properly:



- When you put your safety helmet on, the pre-assembled AirBridge® suspension system should comfortably rest on your head with the brim at eyebrow level
- Height can be adjusted with the variable slots in rear of suspension system for optimized comfort
- Use the one-hand wheel ratchet to ensure a snug fit, but not so tight that it causes discomfort or irritation
- Always wear your safety helmet with the brim of the helmet facing forward

HexArmor[®] Ceros[®] safety helmets are not meant to be worn backward or reversedonned, nor are they tested in this position, and therefore compliance or performance cannot be guaranteed.

The do's and don'ts of caring for your Ceros® safety Helmet

Do: • Perform daily inspections on your helmet and suspension system

- Replace your helmet immediately if it sustains an impact
- · Clean your helmet and suspension system regularly with mild soap and water
- Replace your suspension system every 12 months and your sweatband as needed

Don't: • Store items in or around the suspension system and shell while wearing

- Leave your helmet sitting out in the sunlight after use
- Use paint, chemicals, or other solvents on your helmet
- Modify, engrave, or alter your helmet shell or suspension
- Sit on your safety helmet