## Bad Elf Flex Mini

## Standard | Extreme













## **Key Features**

	Standard	Extreme
Point & track logging	$\checkmark$	✓
Three Bluetooth connections	$\checkmark$	✓
iOS/Android/Windows compatible	$\checkmark$	✓
NMEA Position output	$\checkmark$	✓
1/4"x20 threaded receptacle	$\checkmark$	✓
Third-party app support	$\checkmark$	✓
NTRIP/RTCM3	×	✓
Bad Elf RTK service support	×	✓
Raw logging	×	✓
Tilt function	×	✓
Deviation plot	ж	✓
Datum & orthometric height support*	ж	✓
Laser rangefinder support⁺	×	✓
		† coming soon

## Technical Specs

Multi-constellation: GPS, GLONASS, GALILEO, BEIDOU, QZSS

Multi-frequency: L1 + L5

**Dimensions:** 1.8" x 1.27" x 3.6" (45.7mm x 32.5mm x 91mm)

Weight: 5oz (143g)

Operating Temperature: -4 to 131 °F (-20 to 55 °C)

Battery Life (hrs): All day (24 hours)

USB: Type C, 5V DC, 500 mA

Standard Accuracy w/SBAS: 150 cm horizontal, 3 m vertical (CEP) Extreme Accuracy w/SBAS: 100 cm horizontal, 2 m vertical (CEP)

Extreme Accuracy w/RTK: 25 cm horizontal, 50 cm vertical (CEP)

© 2023 Bad Elf, LLC. Bad Elf and the Bad Elf logos are registered trademarks of Bad Elf, LLC. iPad, iPhone, iPod, and iPod touch are registered trademarks of Apple Inc., registered in the U.S. and other countries. The Bluetooth word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Bad Elf is under license. Other trademarks and trade names are those of their respective owners.

Contact Information

e: sales@bad-elf.com

w: bad-elf.com

p: 1.855.422.3353 x406